



1700

Double Hung

Model	Double Hung - Replacement or New Construction
Series	1700/9400
Class	LCPG25-48" x 80", * LCPG30 44" x 63", *LCPG30 48" x 80", (*Denotes additional reinforcement required)
Operation	Top and Bottom Sash Operable
Sizing	Width - 14 " - 56" Height - 24" - 96" Maximum United Inch Value 146
Glazing	3/4" Insulated assembled with Duralite space (Optional 1" Triple Glazed)
Mulling	Factory and/or Field
Finishes	White/White, White/Pine, Bronze/White, Painted/White, and Painted/Pine
Muntins	Colonial Flat GBG, Colonial Contour GBG and Simulated Divided Lites
Screens	Half or Full Screens
Insulated Glass Options	LowE/Argon, Dual Energy Saver, Fuel Saver, Fuel Saver Plus and Fuel Saver Max

Performance:

The performance numbers listed below represent Interstate Windows Independent laboratory test at the time of publication. Please contact Interstate Window & Door for the most recent performance data.

Model	Test Size	Performance Class	Structural Load (PSF)	Air AT 25 MPH (cfm/ft ²)	Water (No Penetration) PSF
1700/9400	48" x 80"	LCPG25	37.59	0.14	4.6
	48" x 80"	LCPG30	45.11	0.14	4.6
	44" x 63"	LCPG30	45.11	0.11	5.43

Glass Package	Overall Glazing	U Value - No Grids	SHGC- No Grids	U Value- With Grids	SHGC - With Grids
LowE/Argon	3/4"	0.24	0.28	0.25	0.25
Dual ES	3 /4"	0.21	0.26	0.21	0.25
Fuel Saver	1" (Argon/Argon)	0.19	0.22	0.19	0.20
Fuel Saver Plus	1" (Argon/Krypton)	0.17	0.21	0.17	0.19
Fuel Saver Max	1" (Krypton/Krypton)	0.15	0.22	0.15	0.20