



1700 Single Slider

Model	Single Panel Slider - Replacement or New Construction
Series	1700/9400
Class	LCPG25-72" x 60", * LCPG25 72" x 72" (*Denotes additional reinforcement required)
Operation	One Panel Stationary - One Panel Operable
Sizing	Width - 31 3/4 " - 86" Height - 14 1/2" - 72" Maximum United Inch Value 144
Glazing	3/4" Insulated assembled with Duralite space (Optional 1" Triple Glazed)
Mulling	Factory and/or Field
Finishes	White/White, White/Pine, Bronze/White, Painted/White, and Painted/Pine
Muntins	Colonial Flat GBG, Colonial Contour GBG and Simulated Divided Lites
Screens	Half Screen
Insulated Glass Options	LowE/Argon, Dual Energy Saver, Fuel Saver, Fuel Saver Plus and Fuel Saver Max

Performance:

The performance numbers listed below represent Interstate Windows Independent laboratory test at the time of publication. Please contact Interstate Window & Door for the most recent performance data.

Model	Test Size	Performance Class	Structural Load (PSF)	Air AT 25 MPH (cfm/ft2)	Water (No Penetration) PSF
1700/9400	72" x 60"	LCPG25	37.59	0.15	4.6
	72" x 72"	LCPG25	37.59	0.23	4.6

Glass Package	Overall Glazing	U Value - No Grids	SHGC- No Grids	U Value- With Grids	SHGC - With Grids
LowE/Argon	3/4"	0.25	0.29	0.25	0.26
Dual ES	3 /4"	0.21	0.28	0.21	0.25
Fuel Saver	1" (Argon/Argon)	0.19	0.23	0.19	0.21
Fuel Saver Plus	1" (Argon/Krypton)	0.17	0.22	0.17	0.20
Fuel Saver Max	1" (Krypton/Krypton)	0.15	0.23	0.15	0.21