



1700 3 Lite Slider

Model	Dual Panel Slider - Replacement or New Construction
Series	1700/9400
Class	*RPG15-120" x 72" (*Denotes additional reinforcement required)
Operation	Two End Panels Operable-Center Stationary
Sizing	Width - 56 " - 144" Height - 14 1/2" - 72" Maximum United Inch Value 192
Glazing	3/4" Insulated assembled with Duralite space (Optional 1" Triple Glazed)
Mulling	Factory and/or Field
Finishes	White/White, White/Pine, Bronze/White, Painted/White, and Painted/Pine
Muntins	Colonial Flat GBG, Colonial Contour GBG and Simulated Divided Lites
Screens	Half Screens
Insulated Glass Options	LowE/Argon, Dual Energy Saver, Fuel Saver, Fuel Saver Plus and Fuel Saver Max

Performance:

The performance numbers listed below represent Interstate Windows Independent laboratory test at the time of publication. Please contact Interstate Window & Door for the most recent performance data.

Model	Test Size	Performance Class	Structural Load (PSF)	Air AT 25 MPH (cfm/ft2)	Water (No Penetration) PSF
1700/9400	120" x 72"	RPG15	22.56	0.16	3.76

Glass Package	Overall Glazing	U Value - No Grids	SHGC- No Grids	U Value- With Grids	SHGC - With Grids
LowE/Argon	3/4"	0.25	0.29	0.25	0.26
Dual ES	3 /4"	0.21	0.27	0.21	0.24
Fuel Saver	1" (Argon/Argon)	0.19	0.23	0.19	0.21
Fuel Saver Plus	1" (Argon/Krypton)	0.17	0.22	0.17	0.20
Fuel Saver Max	1" (Krypton/Krypton)	0.15	0.23	0.15	0.21