



1700 2 Panel Patio Door

Model	2 Panel Patio Door - Replacement or New Construction
Series	1700/9400
Class	LCPG30-96" x 96"
Operation	One Fixed Panel - One Operable Panel
Sizing	Width - 50" - 96" Height - 72" - 96" Maximum United Inch Value 192
Glazing	1" Tempered Insulated Glass
Mulling	Factory/Field
Finishes	White/White, White/Pine, Bronze/White, Painted/White, and Painted/Pine
Muntins	Colonial Flat GBG, Colonial Contour GBG and Simulated Divided Lites
Screens	Half Screen
Insulated Glass Options	LowE/Argon, Fuel Saver, Fuel Saver Plus and Fuel Saver Max

Performance:

The performance numbers listed below represent Interstate Windows Independent laboratory test at the time of publication. Please contact Interstate Window & Door for the most recent performance data.

Model	Test Size	Performance Class	Structural Load (PSF)	Air AT 25 MPH (cfm/ft2)	Water (No Penetration) PSF
1700/9400	96" x 96"	LCPG30	45.1	0.19	4.6

Glass Package	Overall Glazing	U Value - No Grids	SHGC- No Grids	U Value- With Grids	SHGC - With Grids
LowE/Argon	3/4"	0.27	0.30	0.27	0.27
Fuel Saver	1" (Argon/Argon)	0.20	0.24	0.20	0.21
Fuel Saver Plus	1" (Argon/Krypton)	0.17	0.23	0.18	0.21
Fuel Saver Max	1" (Krypton/Krypton)	0.16	0.24	0.16	0.21