



**1700**  
**Picture Window**  
**Insert Sash**

Model	Picture window insert sash - Replacement or New Construction
Series	1700/9400
Class	LCPG35 60" x 60", LCPG30-70" x 84" (*Denotes additional reinforcement required)
Operation	Stationary
Sizing	Width - 14 " - 96" Height - 14" - 96" Maximum United Inch Value 154
Glazing	3/4" Insulated assembled with Duralite space (Optional 1" Triple Glazed)
Mulling	Factory and/or Field
Finishes	White/White, White/Pine, Bronze/White, Painted/White, and Painted/Pine
Muntins	Colonial Flat GBG, Colonial Contour GBG and Simulated Divided Lites
Screens	Not Available
Insulated Glass Options	LowE/Argon, Dual Energy Saver, Fuel Saver, Fuel Saver Plus and Fuel Saver Max

**Performance:**

The performance numbers listed below represent Interstate Windows Independent laboratory test at the time of publication. Please contact Interstate Window & Door for the most recent performance data.

Model	Test Size	Performance Class	Structural Load (PSF)	Air AT 25 MPH (cfm/ft <sup>2</sup> )	Water (No Penetration) PSF
1700/9400	60" x 60"	LCPG35	52.5	0.03	12
	70" x 84"	LCPG30	45	0.03	12

**\*\*Based on Single Strength Glass\*\***

Glass Package	Overall Glazing	U Value - No Grids	SHGC- No Grids	U Value- With Grids	SHGC - With Grids
LowE/Argon	3/4"	0.24	0.29	0.24	0.26
Dual ES	3 /4"	0.21	0.28	0.21	0.25
Fuel Saver	1" (Argon/Argon)	0.18	0.23	0.19	0.21
Fuel Saver Plus	1" (Argon/Krypton)	0.16	0.22	0.17	0.20
Fuel Saver Max	1" (Krypton/Krypton)	0.15	0.23	0.15	0.21