



1750 Awning

Model	Awning - Replacement
Series	1750/9800
Class	LCPG30-60" x 36" (*Denotes additional reinforcement required)
Operation	Crank out
Sizing	Width - 16 " - 60" Height - 13 1/2" - 36" Maximum United Inch Value 96
Glazing	3/4" Insulated assembled with Duralite space (Optional 1" Triple Glazed)
Mulling	Factory and/or Field
Finishes	White/White, White/Pine, Bronze/White, Painted/White, and Painted/Pine
Muntins	Colonial Flat GBG, Colonial Contour GBG and Simulated Divided Lites
Screens	Full Screen
Insulated Glass Options	LowE/Argon, Dual Energy Saver, Fuel Saver, Fuel Saver Plus and Fuel Saver Max

Performance:

The performance numbers listed below represent Interstate Windows Independent laboratory test at the time of publication. Please contact Interstate Window & Door for the most recent performance data.

Model	Test Size	Performance Class	Structural Load (PSF)	Air AT 25 MPH (cfm/ft ²)	Water (No Penetration) PSF
1750/9800					
	60" x 36"	LCPG30	45.11	0.03	7.52

Glass Package	Overall Glazing	U Value - No Grids	SHGC- No Grids	U Value- With Grids	SHGC - With Grids
LowE/Argon	3/4"	0.23	0.27	0.23	0.24
Dual ES	3/4"	0.19	0.26	0.19	0.23
Fuel Saver	1" (Argon/Argon)	0.18	0.21	0.18	0.20
Fuel Saver Plus	1" (Argon/Krypton)	0.16	0.21	0.16	0.19
Fuel Saver Max	1" (Krypton/Krypton)	0.14	0.21	0.14	0.19