



1750 Casement

Model	Casement - Replacement
Series	1750/9800
Class	LCPG40-36" x 72" (*Denotes additional reinforcement required)
Operation	Crank out - Hinged Left or Right
Sizing	Width - 13 1/4" - 36" Height - 20" - 80" Maximum United Inch Value 116
Glazing	3/4" Insulated assembled with Duralite space (Optional 1" Triple Glazed)
Mulling	Factory and/or Field
Finishes	White/White, White/Pine, Bronze/White, Painted/White, and Painted/Pine
Muntins	Colonial Flat GBG, Colonial Contour GBG and Simulated Divided Lites
Screens	Full Screen
Insulated Glass Options	LowE/Argon, Dual Energy Saver, Fuel Saver, Fuel Saver Plus and Fuel Saver Max

Performance:

The performance numbers listed below represent Interstate Windows Independent laboratory test at the time of publication. Please contact Interstate Window & Door for the most recent performance data.

Model	Test Size	Performance Class	Structural Load (PSF)	Air AT 25 MPH (cfm/ft ²)	Water (No Penetration) PSF
1750/9800					
	36" x 72"	LCPG40	60.15	0.02	11.28

Glass Package	Overall Glazing	U Value - No Grids	SHGC- No Grids	U Value- With Grids	SHGC - With Grids
LowE/Argon	3/4"	0.23	0.26	0.23	0.24
Dual ES	3/4"	0.19	0.25	0.19	0.23
Fuel Saver	1" (Argon/Argon)	0.17	0.21	0.18	0.19
Fuel Saver Plus	1" (Argon/Krypton)	0.15	0.20	0.16	0.19
Fuel Saver Max	1" (Krypton/Krypton)	0.14	0.21	0.14	0.19