



# 1750 Commercial Double Hung

Model	Double Hung - Replacement
Series	1750/9900
Class	*HC30 56" x 91", *HC50 39" x 60" (*Denotes additional reinforcement required)
Operation	Top and Bottom Sash Operable
Sizing	Width - 14 1/2" - 57"    Height - 24" - 96"    Maximum United Inch Value 148
Glazing	3/4" Insulated assembled with Duralite space (Optional 1" Triple Glazed)
Mulling	Factory and/or Field
Finishes	White/White, White/Pine, Bronze/White, Painted/White, and Painted/Pine
Muntins	Colonial Flat GBG, Colonial Contour GBG and Simulated Divided Lites
Screens	Half or Full Screens
Insulated Glass Options	LowE/Argon, Dual Energy Saver, Fuel Saver, Fuel Saver Plus and Fuel Saver Max

**Performance:**

The performance numbers listed below represent Interstate Windows Independent laboratory test at the time of publication. Please contact Interstate Window & Door for the most recent performance data.

Model	Test Size	Performance Class	Structural Load (PSF)	Air AT 25 MPH (cfm/ft2)	Water (No Penetration) PSF
1750/9900	56" x 91"	HC30	45.14	0.05	7.52
	39" x 60"	HC50	112.85	0.05	7.52

Glass Package	Overall Glazing	U Value - No Grids	SHGC- No Grids	U Value- With Grids	SHGC - With Grids
LowE/Argon	3/4"	0.25	0.27	0.25	0.24
Dual ES	3 /4"	0.21	0.26	0.21	0.23
Fuel Saver	1" (Argon/Argon)	0.19	0.22	0.19	0.19
Fuel Saver Plus	1" (Argon/Krypton)	0.17	0.21	0.17	0.19
Fuel Saver Max	1" (Krypton/Krypton)	0.16	0.21	0.16	0.19
Sothern	3/4"	0.25	0.19	0.25	0.17