



**1750**  
**Direct Set Picture**  
**Window**

Model	Direct Set Picture Window - Replacement
Series	1750/9800
Class	CWPG05-120" x 72" (*Denotes additional reinforcement required)
Operation	Stationary
Sizing	Width - 12" - 120" Height - 12" - 120" Maximum United Inch Value 192
Glazing	3/4" Insulated assembled with Duralite space (Optional 1" Triple Glazed)
Mulling	Factory and/or Field
Finishes	White/White, White/Pine, Bronze/White, Painted/White, and Painted/Pine
Muntins	Colonial Flat GBG, Colonial Contour GBG and Simulated Divided Lites
Screens	Not Available
Insulated Glass Options	LowE/Argon, Dual Energy Saver, Fuel Saver, Fuel Saver Plus and Fuel Saver Max

**Performance:**

The performance numbers listed below represent Interstate Windows Independent laboratory test at the time of publication. Please contact Interstate Window & Door for the most recent performance data.

Model	Test Size	Performance Class	Structural Load (PSF)	Air AT 25 MPH (cfm/ft <sup>2</sup> )	Water (No Penetration) PSF
1750/9800					
	120" x 72"	CWPG50	75.19	<0.01	12.11

**\*\*Based on Single Strength Glass\*\***

Glass Package	Overall Glazing	U Value - No Grids	SHGC- No Grids	U Value- With Grids	SHGC - With Grids
LowE/Argon	3/4"	0.24	0.35	0.24	0.32
Dual ES	3 /4"	0.20	0.33	0.20	0.30
Fuel Saver	1" (Argon/Argon)	0.17	0.28	0.18	0.25
Fuel Saver Plus	1" (Argon/Krypton)	0.15	0.27	0.15	0.25
Fuel Saver Max	1" (Krypton/Krypton)	0.13	0.28	0.13	0.25