



1750 Double Hung

Model	Double Hung - Replacement
Series	1750/9800
Class	LCPG35-48" x 78", * LCPG40 48" x 78", *LCPG35 40" x 63", *LCPG40 40" x 63" (*Denotes additional reinforcement required)
Operation	Top and Bottom Sash Operable
Sizing	Width - 14 1/2 " - 53" Height - 24" - 86" Maximum United Inch Value 137
Glazing	3/4" Insulated assembled with Duralite space (Optional 1" Triple Glazed)
Mulling	Factory and/or Field
Finishes	White/White, White/Pine, Bronze/White, Painted/White, and Painted/Pine
Muntins	Colonial Flat GBG, Colonial Contour GBG and Simulated Divided Lites
Screens	Half or Full Screens
Insulated Glass Options	LowE/Argon, Dual Energy Saver, Fuel Saver, Fuel Saver Plus and Fuel Saver Max

Performance:

The performance numbers listed below represent Interstate Windows Independent laboratory test at the time of publication. Please contact Interstate Window & Door for the most recent performance data.

Model	Test Size	Performance Class	Structural Load (PSF)	Air AT 25 MPH (cfm/ft2)	Water (No Penetration) PSF
1750/9800	48" x 78"	LCPG35	52.66	0.16	5.43
	48" x 78"	LCPG40	60.19	0.16	6.06
	40" x 63"	LCPG35	52.66	0.12	5.43
	40" x 63"	LCPG50	75.24	0.12	7.52

Glass Package	Overall Glazing	U Value - No Grids	SHGC- No Grids	U Value- With Grids	SHGC - With Grids
LowE/Argon	3/4"	0.24	0.27	0.24	0.24
Dual ES	3 /4"	0.21	0.26	0.21	0.23
Fuel Saver	1" (Argon/Argon)	0.19	0.22	0.19	0.19
Fuel Saver Plus	1" (Argon/Krypton)	0.17	0.21	0.17	0.19
Fuel Saver Max	1" (Krypton/Krypton)	0.15	0.21	0.16	0.19