



1750 Picture Window Insert Sash

Model	Picture window insert sash - Replacement
Series	1750/9800
Class	FWC35 (*Denotes additional reinforcement required)
Operation	Stationary
Sizing	Width - 12 " - 84" Height - 14" - 84" Maximum United Inch Value 156
Glazing	3/4" Insulated assembled with Duralite space (Optional 1" Triple Glazed)
Mulling	Factory and/or Field
Finishes	White/White, White/Pine, Bronze/White, Painted/White, and Painted/Pine
Muntins	Colonial Flat GBG, Colonial Contour GBG and Simulated Divided Lites
Screens	Not Available
Insulated Glass Options	LowE/Argon, Dual Energy Saver, Fuel Saver, Fuel Saver Plus and Fuel Saver Max

Performance:

The performance numbers listed below represent Interstate Windows Independent laboratory test at the time of publication. Please contact Interstate Window & Door for the most recent performance data.

Model	Test Size	Performance Class	Structural Load (PSF)	Air AT 25 MPH (cfm/ft2)	Water (No Penetration) PSF
1750/9800	60" x 78"	FWC35	52.66	<0.01	6.06

****Based on Single Strength Glass****

Glass Package	Overall Glazing	U Value - No Grids	SHGC- No Grids	U Value- With Grids	SHGC - With Grids
LowE/Argon	3/4"	0.24	0.28	0.24	0.25
Dual ES	3 /4"	0.20	0.27	0.20	0.24
Fuel Saver	1" (Argon/Argon)	0.18	0.23	0.19	0.20
Fuel Saver Plus	1" (Argon/Krypton)	0.16	0.22	0.16	0.20
Fuel Saver Max	1" (Krypton/Krypton)	0.14	0.22	0.15	0.20