



# 440 Double Hung

Model	Double Hung - Replacement or New Construction
Series	440/6800
Class	LCPG40-40" x 63", *LCPG55 40" x 63", RPG20 48" x 78", LCPG25 48" x 78", *LCPG30 48" x 78" (*Denotes additional reinforcement required)
Operation	Top and Bottom Sash Operable
Sizing	Width - 15 1/2" - 48" Height - 24" - 78" Maximum United Inch Value 147
Glazing	3/4" Insulated assembled with Duralite space (Optional 1 1/4" Triple Glazed)
Mulling	Factory and/or Field
Finishes	White/White, Clay/Clay, White/wood Laminate, Painted/White
Muntins	Colonial Flat GBG, Colonial Contour GBG and Simulated Divided Lites
Screens	Half or Full Screens
Insulated Glass Options	Low E/Argon, Dual Energy Saver, Fuel Saver and Southern

**Performance:**

The performance numbers listed below represent Interstate Windows Independent laboratory test at the time of publication. Please contact Interstate Window & Door for the most recent performance data.

Model	Test Size	Performance Class	Structural Load (PSF)	Air AT 25 MPH (cfm/ft2)	Water (No Penetration) PSF
440/6800	48" x 78"	RPG20	30.08	0.05	8.35
	48" x 78"	LCPG25	37.59	0.05	8.35
	48" X 78"	LCPG30	45.11	0.05	8.35
	40" x 63"	LCPG40	60.15	0.05	8.35
	40" x 63"	LCPG55	90.23	0.05	8.35

Glass Package	Overall Glazing	U Value - No Grids	SHGC- No Grids	U Value- With Grids	SHGC - With Grids
LowE/Argon	3/4"	0.26	0.30	0.26	0.27
Dual ES	3/4"	0.23	0.29	0.23	0.26
Fuel Saver	1 1/4" (Argon/Argon)	0.16	0.24	0.16	0.22
Southern	3/4"	0.26	0.21	0.26	0.19