



440 DUAL SLIDER

Model	Dual Horizontal Slider - New Construction or Replacement
Series	440/6800
Class	*RPG15-71" x 56" , *RPG20 - 71" x 56" (*Denotes additional reinforcement required)
Operation	Both Panels Operate
Sizing	Width - 23" - 84" Height - 14 1/2" - 66" Maximum United Inch Value 146
Glazing	3/4" Insulated assembled with Duralite space (Optional 1 1/4" Triple Glazed)
Mulling	Factory and/or Field
Finishes	White/White, Clay/Clay, White/wood Laminate, Painted/White
Muntins	Colonial Flat GBG, Colonial Contour GBG and Simulated Divided Lites
Screens	Half or Full Screen
Insulated Glass Options	LowE/Argon, Dual Energy Saver, Fuel Saver, and Southern Glass

Performance:

The performance numbers listed below represent Interstate Windows Independent laboratory test at the time of publication. Please contact Interstate Window & Door for the most recent performance data.

Model	Test Size	Performance Class	Structural Load (PSF)	Air AT 25 MPH (cfm/ft2)	Water (No Penetration) PSF
440/8800	71" x 56"	RPG15	22.56	0.13	6.89
	71" x 56"	RPG20	30.08	0.13	6.89

Glass Package	Overall Glazing	U Value - No Grids	SHGC- No Grids	U Value- With Grids	SHGC - With Grids
LowE/Argon	3/4"	0.26	0.29	0.26	0.26
Dual ES	3/4"	0.23	0.29	0.23	0.26
Fuel Saver	1 1/4" (Argon/Argon)	0.16	0.23	0.16	0.21
Southern	3/4"	0.26	0.21	0.26	0.19