



440 Awning

Model	Awning - New Construction or Replacement
Series	440/6800
Class	LCPG25-60" x 40" , *LCPG30 - 60" x 40" , LCPG50-48" x 32" (*Denotes additional reinforcement required)
Operation	Crank out
Sizing	Width - 14 1/2" - 60" Height - 13 3/4" - 36" Maximum United Inch Value 96
Glazing	3/4" Insulated assembled with Duralite space (Optional 1 1/4" Triple Glazed)
Mulling	Factory and/or Field
Finishes	White/White, Clay/Clay, White/Wood Laminate, Painted/White
Muntins	Colonial Flat GBG, Colonial Contour GBG and Simulated Divided Lites
Screens	Full Screen
Insulated Glass Options	LowE/Argon, Dual Energy Saver, Fuel Saver, and Southern Glass

Performance:

The performance numbers listed below represent Interstate Windows Independent laboratory test at the time of publication. Please contact Interstate Window & Door for the most recent performance data.

Model	Test Size	Performance Class	Structural Load (PSF)	Air AT 25 MPH (cfm/ft ²)	Water (No Penetration) PSF
440/8800	60" x 40"	LCPG25	37.59	0.04	9.82
	60" x 40"	LCPG30	45.11	0.04	9.82
	48" x 32"	LCPG50	75.19	0.04	9.82

Glass Package	Overall Glazing	U Value - No Grids	SHGC- No Grids	U Value- With Grids	SHGC - With Grids
LowE/Argon	3/4"	0.25	0.30	0.25	0.27
Dual ES	3/4"	0.22	0.29	0.22	0.26
Fuel saver	1 1/8" (Argon/Argon)	0.18	0.24	0.18	0.22
Fuel Saver Plus	1 1/8" (Argon/Krypton)	0.15	0.24	0.15	0.22
Southern	3/4"	0.25	0.21	0.25	0.19