



440
Direct Set
Picture Window

Model	Picture Window - Replacement or New Construction
Series	440/6800
Class	CWPG35 96" x 72" (*Denotes additional reinforcement required)
Operation	Stationary
Sizing	Width - 14 1/4" - 84" Height - 13 1/4" - 84" Maximum United Inch Value 156
Glazing	3/4" Insulated assembled with Duralite space (Optional 1 1/4" Triple Glazed)
Mulling	Factory and/or Field
Finishes	White/White, Clay/Clay, White/Wood Laminate, Painted/White
Muntins	Colonial Flat GBG, Colonial Contour GBG and Simulated Divided Lites
Screens	Not Available
Insulated Glass Options	LowE/Argon, Dual Energy Saver, Fuel Saver and Southern

Performance:

The performance numbers listed below represent Interstate Windows Independent laboratory test at the time of publication. Please contact Interstate Window & Door for the most recent performance data.

Model	Test Size	Performance Class	Structural Load (PSF)	Air AT 25 MPH (cfm/ft2)	Water (No Penetration) PSF
440/8800					
	96" x 72"	CWPG35	52.63	<0.01	12.11

Glass Package	Overall Glazing	U Value - No Grids	SHGC- No Grids	U Value- With Grids	SHGC - With Grids
LowE/Argon	3/4"	0.24	0.33	0.24	0.30
Dual ES	3/4"	0.21	0.32	0.21	0.29
Fuel Saver	1 1/8" (Argon/Argon)	0.17	0.26	0.17	0.24
Fuel Saver Plus	1 1/8" (Argon/Krypton)	0.14	0.26	0.14	0.24
Southern	3/4"	0.24	0.23	0.24	0.21