INTERSTATE Building Materials, Inc.

145 Double Hung

Model	Double Hung - Replacement or New Construction
Series	145/5000/5100
Class	*HR50-38" x 62", *RPG45 40" x 63", *RPG35 40" x 63", *RPG20 48" x 78" (*Denotes additional reinforcement required)
Operation	Top and Bottom Sash Operable
Sizing	Width - 15 3/4" - 48" Height - 24" - 78" Maximum United Inch Value 126
Glazing	3/4" Insulated assembled with Duralite spacer
Mulling	Factory and/or Field
Finishes	White/White, Painted/White
Muntins	Colonial Flat GBG, Colonial Contour GBG
Screens	Half or Full Screens
Insulated Glass Options	Low E/Argon, Dual Energy Saver and Heatguard

Performance:

The performance numbers listed below represent Interstate Windows Independent laboratory test at the time of publication. Please contact Interstate Window & Door for the most recent performance data.

Model	Test Size	Performance Class	Structural Load (PSF)	Air AT 25 MPH (cfm/ft2)	Water (No Penetration) PSF
145/5000/5200	48" x 78"	RPG20	37.59	0.13	6.89
	40" x 63"	RPG35	52.66	0.09	7.52
	40" x 63"	RPG45	67.67	0.11	7.52
	38" x 62"	HR50	75.24	0.09	7.52

Glass Package	Overall Glazing	U Value - No Grids	SHGC- No Grids	U Value- With Grids	SHGC - With Grids
LowE/Argon	3 /4"	0.27	0.30	0.27	0.27
Dual ES	3/4"	0.24	0.29	0.24	0.26
Heatguard	3/4"	0.27	0.22	0.27	0.20